

TimberBlindMetroShade

TBMS50 Programming

These directions are for programming a motor from a factory default state. If the shade has been programmed and other adjustments need to be made, additional directions will be at the end of this document. Please read entire document before programming.

STEP 1 To pair a remote to a shade

- 1.Press the programming button on the motor once and release quickly. (Shade will beep)
- 2.Press P2 on the remote. (Shade will beep)
- 3.Press P2 on the remote. (Shade will beep)
- 4.Press the up or down arrow on the remote. (Shade will jog & beep)

The remote will now work with the shade.

STEP 2 Limit Setting Mode

- 1.Press P2 on the remote. (Shade will beep)
- 2.Press the up arrow on the remote. (Shade will beep)
- 3.Press P2 on the remote. (Shade will jog & beep 1 time to confirm that you are in limit setting mode)

Now you can set the limits.

STEP 3 Setting limits

- 1.Move the shade to the desired upper position, stop the shade and continue to hold the stop button until the shade jogs. The upper limit is now set.
- 2.Move the shade to the desired lower position, stop the shade and continue to hold the stop button until the shade jogs. The lower limit is now set.
- 3.If limits need to be adjusted after setting, go back to Limit Setting Mode and follow Setting Limits

STEP 4 Setting 3rd Limit, Intermediate Position

- 1.Move shade to the desired intermediate position.
- 2.Press P2 on the remote. (Shade will beep)
- 3.Press stop on remote. (Shade will beep)
- 4.Press stop on the remote. (Shade will jog & beep)

The intermediate stop is set. To activate the 3rd limit, press the stop button for approximately 2-3 seconds. Shade will move to the intermediate position.

STEP 5 To remove 3rd Limit, Intermediate Position

- 1.Press stop button for about 5 seconds, shade will move to Intermediate Position
- 2.Press P2 on the remote. (Shade will beep)
- 3.Press stop button on the remote. (Shade will beep)
- 4.Press stop button on the remote. (Shade will jog once and beep 4 times)

3rd limit is now removed.

STEP 6 Adding a remote.

- 1.Press P2a (Shade will beep)
- 2.Press P2a (Shade will beep)
- 3.Press P2b (Shade will jog)

P2 = Working remote, P2b = Remote to add

STEP 7 Removing a remote.

If you remove a remote, all remotes will be removed. Shade will have to be paired again and limits set.

- 1.Press P2a or P2b (Shade will beep)
- 2.Press stop on a or b (Shade will beep)
- 3.Press P2a or P2b (Shade will jog & beep)

All remotes have been deleted.

STEP 8 About programming button

- 1.Press once and release quickly, shade will beep indicating it's ready to be paired with a remote.
- 2.Press and hold for about 5 sec, shade will jog. This will reverse motor direction.

Additional Information:

Location of P2 on remote



Location of programming button

